

delivery auger system to the feed bin.

[Learn More](#)

FLEX-AUGER System has proven to be the most reliable and best system ever devised to deliver feed.

[Learn More](#)

[Learn More](#)

[See More](#)

Specifications

Feed Bin Capacities


Model	Hopper Angle	Capacity (40 lb/cu ft Tons)	Capacity (641 kg/m ³ Metric Tons)	Volume	Height to Fill
6 ft diameter bins					
45-00601	60°	3.1	2.8	156.9 cu ft (4.44 m ³)	11 ft 6 in. (3.5 m)
45-00602	60°	4.6	4.2	231.9 cu ft (6.57 m ³)	14 ft 2 in. (4.3 m)
45-00603	60°	6.1	5.6	306.9 cu ft (8.69 m ³)	16 ft 10 in. (5.1 m)
45-00604	60°	7.6	6.9	381.9 cu ft (10.81 m ³)	19 ft 6 in. (5.9 m)

7 ft diameter bins						
45-00721	67°	4.9	4.5	245.6 cu ft (6.95 m ³)	14 ft 9 in. (4.5 m)	
45-00722	67°	6.9	6.3	347.0 cu ft (9.83 m ³)	17 ft 5 in. (5.3 m)	
45-00723	67°	9.0	8.1	448.4 cu ft (12.70 m ³)	20 ft 1 in. (6.1 m)	
45-00724	67°	11.0	10.0	549.8 cu ft (15.57 m ³)	22 ft 9 in. (6.9 m)	
45-00725	67°	13.0	11.8	651.2 cu ft (18.44 m ³)	25 ft 5 in. (7.7 m)	
45-00726	67°	15.1	13.7	752.6 cu ft (21.31 m ³)	28 ft 1 in. (8.6 m)	
9 ft diameter bins						
45-00901	60°	8.6	7.8	427.6 cu ft (12.11 m ³)	15 ft 7 in. (4.8 m)	
45-00902	60°	12.0	10.8	597.6 cu ft (16.92 m ³)	18 ft 3 in. (5.6 m)	
45-00903	60°	15.4	13.9	767.6 cu ft (21.74 m ³)	20 ft 11 in. (6.4 m)	
45-00904	60°	18.8	17.0	937.6 cu ft (26.55 m ³)	23 ft 7 in. (7.2 m)	
45-00905	60°	22.2	20.1	1,107.6 cu ft (31.36 m ³)	26 ft 3 in. (8.0 m)	

45-00906	60°	25.6	23.2	1,277.6 cu ft (36.18 m ³)	28 ft 11 in. (8.8 m)
45-00907	60°	28.9	26.2	1,442.6 cu ft (40.85 m ³)	31 ft 7 in. (9.6 m)
12 ft diameter bins					
45-01201	60°	17.8	16.1	887.5 cu ft (25.13 m ³)	19 ft 5 in. (5.9 m)
45-01202	60°	23.7	21.5	1,186. cu ft (33.58 m ³)	22 ft 1 in. (6.7 m)
45-01203	60°	29.7	26.9	1,484.4 cu ft (42.03 m ³)	24 ft 9 in. (7.5 m)
45-01204	60°	35.7	32.3	1,782.9 cu ft (50.49 m ³)	27 ft 5 in. (8.4 m)
45-01205	60°	41.6	37.8	2,081.3 cu ft (58.94 m ³)	30 ft 1 in. (9.2 m)
45-01206	60°	47.6	43.2	2,379.9 cu ft (67.39 m ³)	32 ft 9 in. (10.0 m)
45-01207	60°	53.6	48.6	2,678.3 cu ft (75.84 m ³)	35 ft 5 in. (10.8 m)
15 ft diameter binsr					
45-01502	60°	41.5	37.7	2,076.0 cu ft (58.79 m ³)	25 ft 10 in. (79 m)
45-01503	60°	50.9	46.1	2,542.5 cu ft (72.00 m ³)	28 ft 6 in. (8.7 m)

45-01504	60°	60.2	54.6	3,008.6 cu ft (85.19 m ³)	31 ft 2 in. (9.5 m)
45-01505	60°	69.5	63.0	3,474.9 cu ft (98.40 m ³)	33 ft 10 in. (10.3 m)
45-01506	60°	78.8	71.5	3,941.2 cu ft (111.60 m ³)	36 ft 6 in. (11.1 m)
45-01507	60°	88.2	80.0	4,407.5 cu ft (124.81 m ³)	39 ft 2 in. (11.9 m)
45-01508	60°	97.5	88.4	4,873.8 cu ft (138.01 m ³)	41 ft 10 in. (12.8 m)

Literature



[Brock Aeration Kit For Hopper-Bottom Bins BR-1332-202011 \(427.89kB\)](#)



[Brock Next Generation of Hopper Bins BR-1906-202101 \(1.54MB\)](#)



[Brock Next Generation of Hopper Silos-Metric BR-1906-202101 \(1.55MB\)](#)



[Brock Shaker-Plate® Material Flow Control BR-1595-202106 \(280.71kB\)](#)